

## Quality Certificate **FILAINE**

- |    |                       |   |
|----|-----------------------|---|
| 1. | Material composition: | 100 % acrylic                             |
| 2. | Make-up:              | 1000 m cones                              |
| 3. | Thread count:         | dtex 290 / Nm 34/2<br>Ne 20/2 / den 260/2 |
| 4. | Weights:              | 17.000 m/kg                               |

5.	Fastness:	<i>Standard</i>	<i>Parametre</i>	
	<b>to water</b>	ISO 105 E 01 (DIN 54006)	strict	4
	<b>to washing</b>	ISO 105 C 06 (DIN 54017)	60°C 90°C	4 4
	<b>to dry laundry</b>	EN ISO 105 D 01		4 - 5
	<b>to rubbing</b>	ISO 105 X 12 (DIN 54021)	dry wet	4 4
	<b>to perspiration</b>	ISO 105 E 04 (DIN 54020)	alkaline acid	4/4 - 5 4/4 - 5
	<b>to light</b>	ISO 105 B 01/02 (DIN 54003/04)	day light xenon light	5 5
	<b>to chlorine:</b>			
	<b>*chlorine solution</b>	ISO 105 E 03		4

- |    |                       |            |         |      |
|----|-----------------------|------------|---------|------|
| 6. | Shrinkage:            | A 10 22 02 | %       | 0,8  |
| 7. | Breaking strength:    |            | cN/Text | 13,7 |
| 8. | Elongation:           |            | %       | 22,7 |
| 9. | Washing instructions: |            |         |      |



**FILAINE** – acrylic embroidery thread – is subject to regular and strict quality inspections (e.g. measuring of the coefficient of sliding friction, etc.). Thus you are always sure of getting high quality thread.

