

INFORMACIONES DE PRODUCTO

TELAS DE EFECTO



ARTÍCULO	MATERIAL	ÖKOTEX	COLORES	PRESENTACIÓN	ESPESOR	LAVADO	DESCRIPCIÓN
STEP	100% PES adhesive: 100% HDPE	no	10	75 cm x 3 m	325 g/m ²	40°C	aspecto de bordado tejido
STEP				75 cm x 10 m			
TWILLY	74 % PES / 26 % CO adhesive: 100% HDPE	si	16	40 cm x 3 m	330 gr/m ²	60°C	sarga para logos
TWILLY				40 cm x 10 m			
TWILLY				80 cm x 10 m			
TWILLY SOFT	72% PES / 28% CO adhesive: 100% PA	si	16	40 cm x 3 m	284 gr/m ²	60°C	sarga para logos
TWILLY SOFT				40 cm x 10 m			
TWILLY SOFT				80 cm x 10 m			
CANVAY	100% PES adhesive: 100 % HDPE	si	2	75 cm x 10 m	295 g/m ²	60°C	tejido para impresión
CANVAY SOFT	100 % PES adhesive: 100% PA	si	2	75 cm x 10 m	249 g/m ²	60°C	tejido para impresión
PUFFY PE 10	90-94%PE/ 6-10% additives	no	2	40 cm x 30 cm	45 kg - 125 kg/m ²	60°C	efecto 3 D para gorras, etc.
PUFFY PE 20				40 cm x 30 cm			efecto 3D para T-shirts, etc.
FELTY	100% PES	si	24	100 cm x 10 m	ca. 210 g/m ²	30°C	fieltro
FELTY				100 cm x 3 m			